


Product Description:

- Cylindrical circular hole installation, rectangular screw installation method optional.
- Suitable for applications such as automotive parts, packaging, logistics transportation, metal processing, etc.

Product features:

- Compact size and appearance
- Visible red light



Type	Distance	Beam	Output	Connection	Wiring
OSQ18-AK150VP6 *M ¹⁾	10...150mm	Red	PNP	Cable	Fig.1
OSQ18-AK150VP6Q	10...150mm	Red	PNP	M12 Connetor	Fig.2
OSQ18-AK150VN6 *M ¹⁾	10...150mm	Red	NPN	Cable	Fig.3
OSQ18-AK150VN6Q	10...150mm	Red	NPN	M12 Connetor	Fig.4
OSQ18-AK200VP6 *M ¹⁾	10...200mm	Red	PNP	Cable	Fig.1
OSQ18-AK200VP6Q	10...200mm	Red	PNP	M12 Connetor	Fig.2
OSQ18-AK200VN6 *M ¹⁾	10...200mm	Red	NPN	Cable	Fig.3
OSQ18-AK200VN6Q	10...200mm	Red	NPN	M12 Connetor	Fig.4


Note 1): * M refers to the cable length in meters. If there is no * M in the model, the default cable length is 2 meters.

TECHNICAL SPECIFICATION


OPERATING VOLTAGE	10...30 V DC	AMBIENT TEMPERATURE OPERATION	-25°C...+55°C
RIPPLE VOLTAGE	≤10%	AMBIENT TEMPERATURE STORAGE	-40°C...+70°C
LIGHT SOURCE TYPE	Red LED	CIRCUIT PROTECTION	Short-circuit protection, reverse polarity protection, over-load protection
OUTPUT CHARACTERISTIC	PNP/NPN	PROTECTION DEGREE	IP67
LOAD CURRENT	≤200mA	HOUSING MATERIAL	PBT+ABS
SWITCHING FREQUENCY	400Hz	CONNECTING TYPE	*m TPU cable /M12 connector
ADJUSTMENT OF SENSITIVITY	Unadjustable		

DIMENSIONS

M12 Connector




Cable



INDICATORS

A	Output indicator	Yellow
B	Stable indicator	Green



ELECTRICAL CONNECTION




Fig.1




Fig.2




Fig.3





Fig.4




产品说明:

- 圆柱形圆孔安装，矩形螺丝安装方式可选。
- 适用汽车零部件，包装，物流输送，金属加工等应用。

产品特点:

- 小巧的尺寸外形
- 可见红光



型号	检测距离	光源	输出方式	连接方式	接线图
OSQ18-AK150VP6 *M ¹⁾	10...150mm	红光	PNP	线缆	图1
OSQ18-AK150VP6Q	10...150mm	红光	PNP	M12 连接器	图2
OSQ18-AK150VN6 *M ¹⁾	10...150mm	红光	NPN	线缆	图3
OSQ18-AK150VN6Q	10...150mm	红光	NPN	M12 连接器	图4
OSQ18-AK200VP6 *M ¹⁾	10...200mm	红光	PNP	线缆	图1
OSQ18-AK200VP6Q	10...200mm	红光	PNP	M12 连接器	图2
OSQ18-AK200VN6 *M ¹⁾	10...200mm	红光	NPN	线缆	图3
OSQ18-AK200VN6Q	10...200mm	红光	NPN	M12 连接器	图4


注1): *M表示线缆长度, 单位米, 型号中无*M默认线缆长度为2米。

技术参数


工作电压	10...30 V DC	工作温度	-25°C...+55°C
纹波电压	≤10%	环境温度	-40°C...+70°C
光源	红光	保护电路	短路保护 反极性保护 输出过载保护
输出特性	PNP/NPN	防护等级	IP67
负载电流	≤200mA	外壳	PBT+ABS
开关频率	400Hz	连接方式	*m TPU 线缆 /M12连接器
灵敏度调节	不可调节		

外形尺寸

M12 连接器




线缆



操作指示

A	开关动作指示灯	黄色LED
B	电源稳态指示灯	绿色LED



接线图




图1




图2




图3




图4

