

Z series Digital Counter



- 6 digit LCD
- Remote reset
- Available in 3 bezel shapes



Model	Z72FB*	ZJ2FB*
Order Code	GIZ72FB*	GIZJ2FB*
Power supply	85-265VAC 50/60Hz	12-48VAC/DC
Power consumption	0.8VA	0.4W
Display	6 digit LCD	
Max. count speed	10Hz	
Range	999999	
Accuracy	± 1 count	
Reset	Electrical	
Input	Pulse at same voltage as supply	
Memory	Min 10 years	
Protection	IP54 from front panel	
Operating temperature	-10 to +50°C	
Dimensions (mm)	A = 58.40 x 42.5D, B = 48W x 24H x 36.5D C= 48W x 31.1H x 36.5D	
Panel cut-out (mm)	A= 37 x 24.6, B= 45.5 x 23, C= 37 x 24.6	

* Specify bezel type A= round bezel, B= 24 x 48 bezel, C= screw mount bezel

Z series Digital Hour Counter

- 6 digit LCD
- Remote start and reset
- Available in 3 bezel shapes



Model	Z71FB*	ZJ1FB*
Order Code	GIZ71FB*	GIZJ1FB*
Power supply	85-265VAC 50/60Hz	12-48VAC/DC
Power consumption	0.8VA	0.4W
Display	6 digit LCD	
Resolution	1/10h	
Range	99999.9h	
Accuracy	± 0.02%	
Reset	Electrical	
Terminals	1,2: Input supply, 3: enable, 4: reset	
Memory	Min 10 years	
Protection	IP54 from front panel	
Operating temperature	-10 to +50°C	
Dimensions (mm)	A = 58.40 x 42.5D B = 48W x 24H x 36.5D C= 48W x 31.1H x 36.5D	
Panel cut-out (mm)	A= 37 x 24.6, B= 45.5 x 23, C= 37 x 24.6	

* Specify bezel type A= round bezel, B= 24 x 48 bezel, C= screw mount bezel

HM36 series Hour Counter

- 6 digit
- Total sealed from dust and moisture
- Available in 3 bezel shapes



Model	LA2*F1	LD1*F1
Order Code	GILA2*F1	GILD1*F1
Power supply	90-265VAC 50/60Hz	10-80VDC
Power consumption	0.5VA	0.25VA
Display	6 digit white on black (3.6mm high)	
Resolution	1/10h	
Range	99999.9h	
Accuracy	± 0.02%	
Reset	NA	
Protection	IP66 from front panel	
Operating temperature	-40 to +85°C	
Panel cut-out (mm)	1= 45 x 45, 2= 36.8 x 24.1, 4= 50.80	

* Specify bezel type 1= rectangular bezel, 2= rectangular 2 hole bezel, 4= round 3 hole bezel