

SWITCH DISCONNECTORS & CAM SWITCHES

50A to 1600A switch disconnectors
Handles and shaft extensions



Handles



GEX...D - GEX...E



GAX66



GEX61 - GEX69



GEX...B - GEX...C

Shaft extension



GAX7...A



GEX7...

For the correct choice of handle and shaft extension for the switch disconnector, refer to tables on pages 88-91.

Order code	Characteristics	Qty per pkg	Wt
		n°	[kg]

DIRECT OPERATING HANDLE, PADLOCKABLE ①.
Rotating type with screw fixing on switch disconnector.
Complete with shaft insert.

GEX6 1D	95mm black lever	1	0.340
GEX6 1E	95mm black lever	1	0.052
GEX6 2D	105mm black lever	1	0.268
GEX6 2E	105mm black lever	1	0.266
GEX6 3D	145mm black two-hand lever	1	0.536
GEX6 3E	145mm black two-hand lever	1	0.424
GEX6 4D	360mm black two-hand lever	1	0.612
GEX6 4E	360mm black two-hand lever	1	0.612
GEX6 5D	50mm black lever	1	0.054
GEX6 6D	105mm black lever	1	0.216
GEX6 7D	245mm black two-hand lever	1	0.322
GEX6 8D	285mm black two-hand lever	1	0.328
GEX6 9D	360mm black two-hand lever	1	0.400

DOOR COUPLING HANDLE, PADLOCKABLE, IP65 ①.
Red/yellow rotating type with screw fixing on door.
Shaft extension to order separately.

GAX66②	Pistol grip lever with release, defeatable per UL508A. □7mm ②	1	0.140
GEX6 1	Lever. □7mm	1	0.326
GEX6 4	Two-hand lever □14mm	1	0.486
GEX6 6	Lever. □10mm	1	0.248
GEX6 7	Two-hand lever □14mm	1	0.302
GEX6 8	Two-hand lever □14mm	1	0.312
GEX6 9	Two-hand lever □14mm	1	0.560

DOOR COUPLING HANDLE, PADLOCKABLE, IP65 ①.
Black rotating type with screw fixing on door.
Shaft extension to order separately.

GAX66 B②	Pistol grip lever with release, defeatable per UL508. □7mm ②	1	0.075
GEX6 1B	Lever. □7mm	1	0.334
GEX6 1C	Lever. □7mm	1	0.074
GEX6 2C	Lever. □10mm	1	0.252
GEX6 3C	Two-hand lever □14mm	1	0.302
GEX6 4B	Two-hand lever □14mm	1	0.492
GEX6 4C	Two-hand lever □14mm	1	0.488
GEX6 6B	Lever. □10mm	1	0.246
GEX6 7B	Two-hand lever □14mm	1	0.298
GEX6 8B	Two-hand lever □14mm	1	0.310
GEX6 9B	Two-hand lever □14mm	1	0.550

SHAFT EXTENSION
for door coupling handles.

GAX7 150A	150mm long; □7mm	1	0.090
GAX7 200A	200mm long; □7mm	1	0.112
GAX7 300A	300mm long; □7mm	1	0.160
GEX7 137	137mm long ①, □7mm	1	0.056
GEX7 160	160mm long ①, □14mm	1	0.248
GEX7 191	191mm long ①, □10mm	1	0.154
GEX7 204	204mm long ①, □14mm	1	0.310
GEX7 206	206mm long ①, □7mm	1	0.084
GEX7 310	310mm long ①, □14mm	1	0.480
GEX7 340	340mm long ①, □10mm	1	0.274
GEX7 347	347mm long ①, □7mm	1	0.142
GEX7 500	500mm long ①, □10mm	1	0.408
GEX7 501	501mm long ①, □14mm	1	0.784
GEX7 600	600mm long ①, □14mm	1	0.930

① See tables on pages 88-91 for the correct choice based on the switch disconnector type used.

② Use with GAX7...A extension types only.

Certifications and compliance

Certifications obtained: GOST
Certifications pending: cULus to UL98 / CSA C22.2 n°4 for GAX66... and GAX7...A types.
Compliant with standards: IEC/EN 60947-1, IEC/EN 60947-3.