

INDUSTRIAL SIGNALLING

Xenon Strobe Beacons





Stroboflash

- 15J xenon strobe
- Aluminium base
- Surface or tube mounting
- IP65



Specifications:

Flash rate:	65fpm ±10
Flash energy:	15J
Protection:	IP65
Duty:	Continuous
Temp rating (°C):	-30 to +40
Cable entry:	Through base
Construction:	Aluminium base, polycarbonate lens



Dimensions in mm

Order Code	Mounting	Voltage	Current	Candela	Weight (kg)
SIR2302450*	Surface (N)	12-24VAC/DC	2.5-1.2A	21500(p)	1.5
SIR2311060*		110VAC	130mA	4600(p)	
SIR2324060*		240VAC	150mA	16500(p)	
SIR2302455*	Tube (AG)	12-24VAC/DC	2.5-1.2A	21500(p)	1.66
SIR2311065*		110VAC	130mA	4600(p)	
SIR2324065*		240VAC	150mA	16500(p)	

*Specify colour A = Amber, B = Blue, C = Clear, G = Green, R = Red

Accessories and Spare Parts



SIR3823010

Order Code	Description
SIR3600001*	Stroboflash lens (*Specify colour)
SIR3823010	Stroboflash N wire guard
SIR3999200	15 joule xenon tube

