

Model RM





- 10W rotating beacon for fire, security and commercial applications
- Low voltage lamps for longer life
- Supplied with spare lamp

Order Code	Voltage	Current	Bulb	Weight (kg)
MXRM012*	12VDC ±10%	850mA	12V 10W	0.6
MXRM024*	24VDC ±10%	425mA	24V 10W	
MXRM240*	240VAC ±10%	40mA	12V 8W	0.75

*Specify colour A = Amber, B = Blue, G = Green, R = Red

Specifications:

Flash Rate: 150 rpm
 Protection: IP44
 Cable Entry: Through Base
 Construction: ABS Base, Acrylic Lens
 Mounting: Within 30° of Vertical



Dimensions in mm

Model RA





- 20W rotating beacon for fire, security and commercial applications
- Low voltage lamps for longer life
- Supplied with spare lamp

Order Code	Voltage	Current	Bulb	Weight (kg)
MXRA012*	12VDC ±10%	1.7A	12V 20W	0.65
MXRA024*	24VDC ±10%	0.85A	24V 20W	
MXRA240*	240VAC ±10%	90mA	12V 20W	1.1

*Specify colour A = Amber, B = Blue, G = Green, R = Red

Specifications:

Flash Rate: 150 rpm
 Protection: IP44
 Cable Entry: Through Base
 Construction: ABS Base, Acrylic Lens
 Mounting: Within 30° of Vertical



Dimensions in mm

Accessories and Spare Parts

Order Code	Description
MX90120	12V 8W bulb (RM 240V)
MX90121	12V 10W bulb (RM 12V)
MX90122	24V 10W bulb (RM 24V)
MX90131	12V 20W bulb (RA 12V and 240V)
MX90132	24V 20W bulb (RA 24V)
MX90016*	RM lens (*Specify colour)
MX90014*	RA lens (*Specify colour)

