

Celere series

- Motor driven sirens up to 114dB
- 3 sizes
- Double insulated
- IP43





Order Code*	Voltage	Current	Sound Frequency	Sound Output dB@1m	Weight (kg)
Mini Celere (BA) – continuously rated					
SIR4101210	12VDC	1.3A	1200Hz	97dB	0.3
SIR4102410	24VDC	0.55A	1300Hz	100dB	
Mini Celere					
SIR4101230	12VAC/DC	2.7A	1020Hz	88dB	0.4
SIR4102430	24VAC/DC	1.47A	1350Hz	94dB	
SIR4104830	48VAC/DC	0.85A	1520Hz	100dB	
SIR4111030	110VAC/DC	0.37A	1450Hz	96dB	
SIR4124030	240VAC/DC	0.22A	1730Hz	101dB	
Celere (BA) – continuously rated					
SIR4301210	12VDC	2.5A	950Hz	103dB	0.6
SIR4302410	24VDC	1.1A	950Hz	103dB	
Celere					
SIR4301230	12VAC/DC	9.2A	1020Hz	100dB	1.2
SIR4302430	24VAC/DC	7.8A	1380Hz	109dB	
SIR4304830	48VAC/DC	3.6A	1410Hz	108.5dB	
SIR4311030	110VAC/DC	0.92A	1060Hz	104.5dB	
SIR4324030	240VAC/DC	0.65A	1430Hz	110dB	
Super Celere (BA) – continuously rated					
SIR4501210	12VDC	9.5A	820Hz	114dB	1.5
SIR4502410	24VDC	5.0A	820Hz	114dB	
Super Celere					
SIR4501230	12VAC/DC	13.5A	800Hz	111dB	1.6
SIR4502430	24VAC/DC	7.0A	900Hz	112dB	
SIR4504830	48VAC/DC	6.0A	1060Hz	113.5dB	
SIR4511030	110VAC/DC	1.7A	970Hz	111.5dB	
SIR4524030	240VAC/DC	1.2A	1120Hz	113.5dB	



Specifications:

Duty cycle:	1 min on. 10 min off (BA versions are continuously rated)
Voltage tolerance:	±10%
Protection:	IP43
Temp rating (°C):	-30 to +40
Cable entry:	M12
Construction:	Polycarbonate



Mini Celere



Celere



Super Celere



Dimensions in mm